



Warrior™ 400i/500i CC/CV

Robust inverter welding packages

The reliable multi-process welding equipment designed for heavy duty productivity with up to 500 amps delivered.



Rugged

User Friendly

Powerful

Warrior™ 400i/500i CC/CV power source

Features

- **Multi-Process** – including MMA, MIG/MAG, LiveTig™ and Arc Gouging gives you the flexibility at work:
 - Flux-Cored and Solid wire, 0.8 -1.6 mm.
 - Carbon Arc Gouging up to 9.5 mm (3/8 in.).
 - 6010 (cellulosic) capability.
- **High Duty cycle** – For long runs and various applications giving high productivity.
- **Durable and rugged** – IP23 rating for outdoor and indoor use in rough environment.
- **Easy to use** – Simple and clear user interface for everyone to get started quickly.
- **Robust and ergonomic handles** – Also for mechanical lifting.
- **Sun friendly display** – easy to read outdoor.
- **Inverter technology** – Smaller, lighter and less energy cost, gives you value for money.
- **Generator compatible** – For flexible use in different job sites.
- **Automatic Hot Start/Variable Arc Control** – To support your different demands.
- **Wide input voltage range** to support regional requirements.



Functionality

- **SCT Technology** give you an automatic burn-back function that after every stop leaves the wire-end in perfect shape ready for next start.
- **The TrueArcVoltage™ System**, in combination with an ESAB **PSF™** torch, guarantees that you will weld with the correct arc voltage independent of any voltage drop in the welding cables. This means that you will get the same arc voltage and weld result regardless of whether you are using a short connection cable or extended cables with up to a 35 meter working radius.

Applications

- Fabrication
- Construction
- Pipe line
- Mobile Machinery
- Ship building
- Energy generation
- Repair & Maintenance
- Rental



Main Controls

- Power On/Off
- Digital Volt/Amp Meter
- Over Temperature LED
- Output Voltage / Current Control
- Welding Process Selector
- Stick Mode Selector
- Inductance/Arc Force Control
- Wire feeder control connector
- Resettable Circuit Breaker
- Output Power Connectors

Warrior™ Feed 304 and MobileFeed 300 AVS – wire feeders

Warrior™ Feed 304

The new user friendly and robust feeder.

- **Rugged design** – handle, connectors for tough use.
- **4 roll drive with tach feedback** – for superior wire feeding.
- **Sun-friendly display** – easy to read outdoor.
- **Bobbin cover** – included standard feature for protection.
- **Voltage Pre-set** – support the setting of welding parameters.



MobileFeed 300 AVS

The rugged arc voltage feeder – Withstands tough environment.

- **Totally enclosed**, super impact-resistant case.
- **4 roll drive** – Gives you the feedability and productivity for demanding in field work.



Quality & Environment

- **IP23 rated** – Withstands rain with the fan on.
- **Air tunnel design** – Clean and dirty side in the machine to ensure long-term reliability.
- **Autofan** – Reduces energy consumption and dirt intake.

Options

Cooling unit

Cool 2

Trolley/Wheel kits

Trolley

Wheel kit power source

Wheel kit feeder

Counterbalance arm

For more options and ordering information, please see last page.



Technical data, Warrior™ Feed 304

Power supply, VAC	42
Wire spool capacity, kg	18
Max. spool diameter, mm	300
Wire feed speed, m/min	0.8-25.0
Dimension incl. bobbin cover : (l x w x h), mm	675 x 264 x 418
Weight incl. bobbin cover, kg	14.5
Wire dimensions:	
steel	0.6-1.6
stainless steel	0.6-1.6
aluminium	0.8-1.6
cored wire	0.9-1.6
Temp. working range	-10/+40 C
Enclosure class	IP 23

Technical data, MobileFeed 300AVS

Power supply, VDC	16.5-100
Wire spool capacity, kg	18
Max. spool diameter, mm	300
Wire feed speed, m/min	1.3-20.3
Dimension (l x w x h), mm	526 x 217 x 437
Weight, kg	14.5
Wire dimensions:	
steel	0.8-1.6
stainless steel	0.8-1.6
cored wire	1.2-2.0
Temp. working range	-10/+40 C
Enclosure class	IP 23

Technical data, Water cooling unit

Power supply, from power source,	40V, 50/60Hz
Coolant flow capacity, l/min	1.8
Cooling power, kW	1.0
Max pressure, bar	4.5
Max pressure height to torch, m	8.5
Weight / incl. coolant, kg	15 / 19
Dimensions incl. filler tube (l x w x h) mm	680 x 325 x 230

Ordering information, Power sources


Warrior™ 400i CC/CV, 380-415V	0465 350 884
Warrior™ 500i CC/CV, 380-415V	0465 350 883

Ordering information, Connection cables

70 mm ²	Air cooled	Water cooled
2m length	0459 836 880	0459 836 890
5m length	0459 836 881	0459 836 891
10m length	0459 836 882	0459 836 892
15m length	0459 836 883	0459 836 893
25m length	0459 836 884	0459 836 894
35m length	0459 836 885	0459 836 895

95 mm ²	Air cooled	Water cooled
2m length	0459 836 980	0459 836 990

This arc welding equipment complies with the requirements of IEC/EN 60974-1 and IEC/EN 60974-10 as well as IEC/EN 60974-2 and IEC/EN 60974-5

The symbol  indicates that the welding power source may be used in areas with an increased electrical hazard, i.e. areas where the electrical hazard is increased due to damp and/or the proximity to earthed metal objects.

Technical data Warrior™ 400i CC/CV 500i CC/CV

Mains Supply, 3 ph 50/60HZ, V	380-415, +/-10%	380-415, +/-10%
Mains cable, Ø mm ²	4 x 6	4 x 6
Fuse, slow A,	25	32
Maximum load at:		
100% duty cycle A/V, 3ph	300/32	400/36
60% duty cycle A/V, 3ph	400/36	500/40
Setting range A		
MIG/MAG	16-400	16-500
MMA	16-400	16-500
TIG	5-400	5-500
Open circuit voltage, V	54	54
Idle Power, W	120	120
Efficiency at max. current, %	88	89
Power factor at max current	0.91	0.91
Enclosure class	IP23	IP23
Dimensions (l x w x h) mm	712x325x470	712x325x470
with cooling unit l (x w x h) mm	712x325x700	712x325x700
Weight, kg	59	59
with cooling unit excl coolant, kg	74	74
Operating Temperature, °C	-10 - +40	-10 - +40
Application class	S	S

Ordering information, Feeder

Warrior™ Feed 304	0465 250 880
Warrior™ Feed 304w, water	0465 250 881
MobileFeed 300 AVS	0558 005 728
Guide pin extension kit	0465 508 880

Ordering information, Options

Trolley	0465 510 880
Remote units	
AT1	0459 491 896
AT1 CoarseFine	0459 491 897
M1	0459 491 895
Remote outlet kit power source, 12p	0465 424 880
Remote outlet kit feeder, 23p	0465 451 880
Adapter for Miggy- and Railtrack	0465 451 881
Remote cable M1- 5m	0459 553 880
Remote cable M1- 10m	0459 553 881
Remote cable M1 - 25m	0459 553 883
Cool 2, water cooler	0465 427 880
Wheel Kit, power source	0465 416 880
Wheel kit, Warrior™ feeder	0458 707 880
Stabilizer kit **	0465 509 880
Counterbalance arm	0458 705 880
Multi voltage unit TUA1	0459 144 880
Handle incl. mounting screws for TUA1	0459 307 880

** Required for counterbalance device.

Ordering information, Torches

MIG/MAG	3.0m length	4.5m length
PSF™ 405	0458 401 882	0458 401 883
PSF™ 505	0458 401 884	0458 401 885
PSF™ 410w	0458 400 882	0458 400 883
PSF™ 510w	0458 400 884	0458 400 885

	6.0m length	10.0m length
*MXH™ 300 PP	0700 200 017	0700 200 018
*MXH™ 400w PP	0700 200 015	0700 200 016
*MXH™ 300 PP 45°	-	0700 200 020
MXH™ 400w PP 45°	-	0700 200 019

TIG	4.0m length	8.0m length
TXH™ 201V	0700 300 553	0700 300 556

Gouging	
Flair 600 incl monocable	0468 253 880

* Requires remote outlet kit 23p in feeder.

www.esab.com



COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV
= ISO 9001 =
= ISO 14001 =
= OHSAS 18001 =